


# GALLERY® collection

## Model GR5SV (6.3 R-Value\*) Model GR5S (25 Gauge)




### 2-LAYER CONSTRUCTION 1<sup>5</sup>/<sub>16</sub>" Insulated



① Steel + ② Insulation

### 1-LAYER CONSTRUCTION Non-Insulated



① Steel (Non-Insulated)

## PRODUCT SPECIFICATIONS

- 2-layer construction (Steel + Insulation) on Model GR5SV. Non-insulated Model GR5S.
- 25 gauge patented deep emboss panel with a vertical ribbed pattern. 1<sup>5</sup>/<sub>16</sub>" polystyrene insulation available (Model GR5SV). R-value 6.3\*
- 2" thick frame secured to steel shell with a durable, rust-proof Tog-L-Loc® fastening system.
- Hot-dipped galvanized steel skin with a baked-on primer and top coat helps assure durability and long-lasting beauty.
- Nylon rollers for durable, smooth, long-lasting performance.
- Patented Safe-T-Bracket® designed for added safety; under normal circumstances it cannot be removed while the door is under tension.
- Shiplap joints and bottom weatherseal in a rust-proof aluminum retainer help seal out the elements.
- 12" radius track for normal installations. 15" radius track available.
- Extension springs standard on single doors (up to and including 10'). EZ-SET® torsion springs standard on all double doors (greater than 10' wide).
- Inside slide lock is standard, outside keyed lock available (at additional charge).
- Spade Lift Handles and Spade Step Plate are standard.

## STYLE & FINISH

- Patented deep emboss panel stamp is available ONLY in the Short Emboss Panel (GR5SV, GR5S).
- Finish may be painted to complement the home's exterior.
- Windows are made from 1/8" DSB or Obscure glass with optional Snap-In grilles. The window frames and grilles are UV-protected. Acrylic Wrought Iron windows also available.

## SIZES

- Available in heights from 6' to 12' in 3" increments.
- Models GR5SV and GR5S doors available in 2" wide increments from 6' to 18' wide.

### EXCEPTIONS

- Doors not available in widths from 10'2" through 11'4" or 14'8".
- Windows not available on 14'10" and 15'4" widths.
- Door widths requiring single spade handle or Twisted "T" design keyed lock: 6'2", 6'4", 6'6", 7'8", 7'10", 11'6", 11'8", 11'10" and 14'10" through 15'10".

## SPECIAL NOTES

- For doors sold through Home Depot's Expert Installation Program, the springing systems and locking systems may vary by market.
- Doors ordered in white unless a color is specified.

\*Calculated door section R-value is in accordance with DASMA TDS-163.


## STANDARD HEADROOM REQUIREMENTS

Extension Springs		Torsion Springs	
Track Radius	Headroom Needed*	Track Radius	Headroom Needed*
12"	10"	12"	12"
15"	12"	15"	14"

\* Add 3" for automatic garage door opener

## MODELS

### Short Panel only



GR5SV / GR5S

## COLORS



White



Almond



Desert Tan



Sandtone



Chocolate

(Printed colors may vary from actual panel colors)

## WINDOWS / TOP SECTIONS




SHORT SOLID



SHORT PLAIN



LONG PLAIN



ARCH WROUGHT IRON



SHORT WROUGHT IRON



ARCH1 PLAIN



ARCH2 PLAIN



ARCH3 PLAIN




ARCH3 GRILLE



SHORT SQUARE GRILLE



LONG SQUARE GRILLE



LONG RECTANGLE GRILLE



LONG WROUGHT IRON



ARCH1 GRILLE



ARCH2 GRILLE



SHORT ASHFORD®



SHORT CLAYTON™



SHORT KRISTIN®



SHORT TRENTON®



LONG ASHFORD®



LONG CLAYTON™



LONG KRISTIN®



LONG TRENTON®

## DECORATIVE HARDWARE

### Standard Hardware:



Spade Lift  
Handles  
(4118684)



Spade  
Step Plate  
(4119015)

See page G4 for complete hardware options.

## WARRANTIES

PAINT SYSTEM  
LIMITED  
15YR  
WARRANTY

WINDOWS  
LIMITED  
10YR  
WARRANTY

HARDWARE  
LIMITED  
3YR  
WARRANTY

