## GALLERY® collection



Constructed of durable steel, this vintage style line is available in long or short grooved panel designs with various windows, colors and hardware options to create that one-of-a-kind look.

## STYLE AND CONSTRUCTION

- Hot-dipped galvanized steel skin with a baked-on primer and top coat helps ensure durability and long-lasting beauty.
- Polystyrene or polyurethane insulation with R-values ranging from 6.3 to 18.4.
- Windows are standard with double strength clear glass and optional snap-in grilles. Other options include Insulated glass, Obscure with snap-in grilles and acrylic wrought iron designs.
- Section joints and bottom weatherseal in a corrosion-resistant aluminum retainer help seal out the elements.

Calculated door section R-value is in accordance with DASMA TDS-163.



COLOR OPTIONS										
White	Almond	Desert Tan	Sandtone	Chocolate*	Ultra-Grain <sup>®</sup> Medium Finish**	Ultra-Grain® Dark Finish**	Ultra-Grain <sup>®</sup> Walnut Finish**			
*Not available on all doors.  *Ultra-Grain**: New Faux woodgrain paint coatings offer the beauty of stained wood without the upkeep. Ultra-Grain* doors have stucco texture.										

<sup>\*\*</sup> Available on 3-layer doors only.

MODEL PANEL STYLE, INSULATION, CONSTRUCTION AND R-VALUE CHART										
MODEL	GD2SU	GD2LU	GD1SU	GD1LU	GD2SP	GD2LP	GD1SP	GD1LP		
Panel Style	Short	Long	Short	Long	Short	Long	Short	Long		
Insulation	2" Polyurethane	2" Polyurethane	1 <sup>3</sup> /8" Polyurethane	1 <sup>3</sup> /8" Polyurethane	2" Polystyrene	2" Polystyrene	1 <sup>3</sup> /8" Polystyrene	1 <sup>3</sup> /8" Polystyrene		
Construction	3-layer	3-layer	3-layer	3-layer	3-layer	3-layer	3-layer	3-layer		
R-value	18.4	18.4	12.9	12.9	9.0	9.0	6.5	6.5		
MODEL	GD4S	GD4L	GD4SV	GD4LV	GD5S	GD5SV				
Panel Style	Short	Long	Short	Long	Short	Short				
Insulation	Non-Insulated	Non-Insulated	Polystyrene	Polystyrene	Non-Insulated	Polystyrene				
Construction	1-layer	1-layer	2-layer	2-layer	1-layer	2-layer				
R-value	N/A	N/A	6.3	6.3	N/A	6.3				

## GALLERY® collection



WINDCODE® AVAILABILITY CHART								
Co	ommon Door Widths	W1	W3	W4	W5	W6	W7	W8
Model GD2SU	8', 9' Wide Door	<b>S</b> +13/–15 PSF	SELECT W4	F S +28/-29 PSF	SELECT W6	F S +38/-42 PSF	SELECT W8	<b>F</b> +54/–60 PSF
	10', 12' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	F S +25.5/-25.5 PSF	<b>F S</b> +30/–30 PSF	● F S +37/-40 PSF	SELECT W8	<b>F</b> +46.6/–52 PSF
GD.	16' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F S</b> +25.5/–25.5 PSF	<b>F S</b> +30/–30 PSF	● F S +37/–40 PSF	SELECT W8	F S +46.6/-52 PSF
	18' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F S</b> +25/-25 PSF	SELECT W6	<b>F</b> +37/–37 PSF		
	8', 9' Wide Door	<b>S</b> +13/–15 PSF	SELECT W4	<b>F S</b> +28/-29 PSF	SELECT W6	F S +38/-42 PSF	SELECT W8	<b>F</b> +54/-60 PSF
Model GD2LU	10', 12' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F S</b> +25.5/–25.5 PSF	<b>F S</b> +30/–30 PSF	<b>► F S</b> +37/–40 PSF	SELECT W8	+46.6/-52 PSF
GD.	16' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F S</b> +25.5/–25.5 PSF	<b>F S</b> +30/–30 PSF	<b>☞ F S</b> +37/–40 PSF	SELECT W8	<b>F</b> +46.6/–52 PSF
	18' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F S</b> +25/-25 PSF	SELECT W6	● F S +37/-37 PSF		
	8', 9' Wide Door	<b>S</b> +13/–15 PSF	SELECT W4	<b>F S</b> +28/–29 PSF	<b>F S</b> +30/–32 PSF			
Model GD1SU	10', 12' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F S</b> +25.5/–25.5 PSF	<b>F S</b> +30/–30 PSF			
© G	16' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F S</b> +25.5/–25.5 PSF	<b>F S</b> +30/–30 PSF			
	18' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F S</b> +25/-25 PSF				
	8', 9' Wide Door	<b>S</b> +13/–15 PSF	F S +20/-20 PSF	SELECT W5	F S +30/–32 PSF			
Model GD1LU	10', 12' Wide Door	<b>S</b> +12.5/–14 PSF	F S +20/-21 PSF	SELECT W5	F S +30/–30 PSF			
GD GD	16' Wide Door	<b>S</b> +12.5/–14 PSF	F S +20/-21 PSF	SELECT W5	<b>F S</b> +30/–30 PSF			
	18' Wide Door	<b>S</b> +12.5/–14 PSF						
	8', 9' Wide Door	<b>S</b> +13/–15 PSF	SELECT W4	F S +28/-29 PSF	SELECT W6	F S +38/-42 PSF	SELECT W8	<b>► F D</b> +54/-60 PSF
Model GD2SP	10', 12' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	F S +25.5/-25.5 PSF	<b>F S</b> +30/–30 PSF	● F S +37/-40 PSF	SELECT W8	F D +46.6/–52 PSF
	16' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	F S +25.5/-25.5 PSF	F S +30/–30 PSF	● F S +37/–40 PSF	SELECT W8	F D +46.6/–52 PSF
	18' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	<b>F</b> +25/-25 PSF		<b>☞ F</b> +37/–37 PSF		

## GALLERY® collection

WINDCODE® AVAILABILITY CHART								
Con	Common Door Widths W1		W3	W4	W5	W6	W7	W8
Model GD2LP	8', 9' Wide Door	<b>S</b> +13/–15 PSF	SELECT W4	F S +28/-29 PSF	SELECT W6	● F S +38/-42 PSF	SELECT W8	<b>▼ F D</b> +54/-60 PSF
	10', 12' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	F S +25.5/-25.5 PSF	F S +30/-30 PSF	● F S +37/-40 PSF	SELECT W8	F D +46.6/–52 PSF
	16' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	F S +25.5/-25.5 PSF	F S +30/–30 PSF	● F S +37/-40 PSF	SELECT W8	F D +46.6/–52 PSF
	18' Wide Door	<b>S</b> +12.5/–14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	F S +37/-37 PSF		
	8', 9' Wide Door	<b>S</b> +13/–15 PSF	<b>F S</b> +20/–20 PSF	SELECT W5	F S +30/-32 PSF			
Model GD1SP	10', 12' Wide Door	<b>S</b> +12.5/–14 PSF	F S +20/-21 PSF	SELECT W5	F S +30/–30 PSF			
M <sub>O</sub> G	16' Wide Door	<b>S</b> +12.5/–14 PSF	<b>F S</b> +20/–21 PSF	SELECT W5	F S +30/-30 PSF			
	18' Wide Door	<b>S</b> +12.5/–14 PSF						
	8', 9' Wide Door	<b>S</b> +13/–15 PSF	F S +20/–20 PSF	SELECT W5	F S +30/–32 PSF			
Model GD1LP	10', 12' Wide Door	<b>S</b> +12.5/–14 PSF	F S +20/-21 PSF	SELECT W5	F S +30/-30 PSF			
₩ G	16' Wide Door	<b>S</b> +12.5/–14 PSF	F S +20/-21 PSF	SELECT W5	F S +30/–30 PSF			
	18' Wide Door	<b>S</b> +12.5/–14 PSF						
ge hort	8', 9' Wide Door	<b>S</b> +13/–15 PSF	SELECT W4	FTS +25/-25 PSF	F T S +30/-32 PSF	● F T S* +37/-37 PSF	SELECT W8	◆ F D +50/–58 PSF
24 gau ® Pan S	10', 12' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	FTS* +25/-25 PSF	F T S* +30/-30 PSF	● F T S* +37/-41 PSF	SELECT W8	F D +46.6/–52 PSF
GD4S 24 gauge Gallery® Pan Short	16' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	FTS* +25/-25 PSF	F T S* +30/–30 PSF	● F T S* +37/-41 PSF	SELECT W8	F D +46.6/–52 PSF
Ğ	18' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	FTS* +25/-25 PSF	SELECT W6	● F S* +37/-39 PSF		
uge Long	8', 9' Wide Door	<b>S</b> +13/–15 PSF	SELECT W4	FTS +25/-25 PSF	SELECT W6	● F T S* +37/-37 PSF		
4 gauge Pan Lon	10', 12' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	FTS* +25/-25 PSF	SELECT W6	● F T S* +37/-41 PSF		
GD4L 24 gau Gallery® Pan L	16' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	FTS* +25/-25 PSF	SELECT W6	● F T S* +37/-41 PSF		
g g	18' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	FTS* +25/-25 PSF				
ry® ited	8', 9' Wide Door	<b>S</b> +13/–15 PSF	SELECT W4	● F S +25/-32 PSF	● F S +30/-32 PS	● <b>F S*</b> +38/–42 PS		
25 gauge Gallery <sup>®</sup> Pan & Pan Insulated	10', 12' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	FS* +24/-24.5 PSF	● F S* +30/-30 PSF	● F S* +37/-41 PSF		
gauge & Pan	16' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	FS* +24/-24.5 PSF	F S* +30/-30 PSF	● F S* +37/–41 PSF		
25 Pan	18' Wide Door	<b>S</b> +12.5/–14 PS	SELECT W4	F S* +24/-24.5 PSF	SELECT W6	<b>● F</b> +37/–37 PSF		
	Standard Windows Ava	ailable		ct Windows Avai la Approved	able	D Dade Cou T Texas Dep	nty Approved artment of Insur	ance Approved

For W6–W8 doors over 9' wide, add 2" to the door opening.
\*Long window availability is limited due to reinforcement requirements.