


**PREMIUM** series

**Models HDP20, HDPL20, HDPF20**  
(18.4 R-VALUE\*)



**3-LAYER CONSTRUCTION**



① Steel + ② Insulation + ③ Steel

**18.4**  
R-VALUE\*  
2" insulation

**PRODUCT SPECIFICATIONS**

- 27 gauge steel skins and insulation are pressure bonded for durable, secure, quiet operation.
- 2" thick polyurethane foamed-in-place insulation with silicone filled thermal break provides superior energy efficiency. **18.4 R-value\***.
- Hot-dipped galvanized steel skin with a baked-on primer and top coat helps assure durability and long-lasting beauty.
- Nylon rollers for durable, smooth, long-lasting performance.
- Patented Safe-T-Bracket® designed for added safety; under normal circumstances it cannot be removed while the door is under tension.
- Tongue-and-groove joints and bottom weatherseal in a rust-proof aluminum retainer helps seal out the elements.
- 12" radius track for normal installations. 15" radius track available.
- Extension springs standard on all single doors (up to and including 10' wide). EZ-SET® torsion springs standard on double doors (greater than 10' wide).
- Inside slide lock is standard, outside keyed lock available (at additional charge).
- Operator reinforcement bracket is standard.

**STYLE AND FINISH**

- Woodgrain texture raised panel and flush designs may be painted with a high quality exterior latex paint to complement any home's exterior.
- Prefinished white end stiles and interior steel provide a clean and finished appearance.

**SIZES**

- Models HDP20 and HDPF20 available in 2" increments from 6'2" to 20' wide.
- Model HDPL20 available in 2" increments from 8' to 20' wide.
- Available in heights from 6' to 12' in 3" increments (excluding 7'3").
- For high lift track applications please call Clopay customer service.

**SPECIAL NOTES**

- For doors sold through Home Depot's Expert Installation Program, the springing systems and locking systems may vary by market.
- Doors ordered in white unless a color is specified.

\*Calculated door section R-value is in accordance with DASMA TDS-163.

**STANDARD HEADROOM REQUIREMENTS**

Extension Springs		Torsion Springs	
Track Radius	Headroom Needed**	Track Radius	Headroom Needed**
12"	10"	12"	12"
15"	12"	15"	14"

\*\*Add 3" for automatic garage door opener.


**PANEL OPTIONS**



HDP20 (Short Elegant)



HDPL20 (Long Elegant)



HDPF20 (Flush)

**COLORS**


White	Almond	Desert Tan	Sandtone
Chocolate	Gray	Hunter Green	
Ultra-Grain® Medium Finish†	Ultra-Grain® Cherry Finish†		

(Printed colors may vary from actual panel colors)  
†Ultra-Grain® not available on Flush models

**WINDOWS**

- Short windows available on Models HDP20 and HDPF20
- Long windows available on Models HDP20, HDPL20, and HDPF20
- Palladian™ Series windows available on top section only
- Plain Series and Snap-In Series (Colonial) windows are standard in 2nd section from top; all other windows standard in top section unless specified otherwise

**Plain Series**



Plain Short

**Snap-In Series**



Prairie 610

**Palladian™ Series**



Long with Grille

See pages S19-S20 for all available window designs and options.

**WARRANTIES**

--	--	--	--