

---

# LEXAN™ CLEANING & CARE INSTRUCTIONS

---

## **CLEANING INSTRUCTIONS**

Wash using a mild soap or detergent (see list of approved cleaning products below) and lukewarm water, using a clean sponge or a soft cloth. Rinse well with clean water. Dry thoroughly with a chamois or moist cellulose sponge to prevent water spots. **Do not scrub or use brushes on this product.**

The following cleaning agents have been found compatible with LEXAN™:

- Joy<sup>1</sup>
- Top Job<sup>1</sup>
- Palmolive Liquid<sup>2</sup>

<sup>1</sup>Registered Trademarks of Procter & Gamble

<sup>2</sup>Registered Trademark of Colgate Palmolive

## **MINIMIZING HAIRLINE SCRATCHES**

Scratches and minor abrasions can be minimized by using a mild automobile polish. It is recommended that a small area be tested with the product selected following the manufacturer's recommended instructions prior to use on a complete window. Listed below are 3 products that are marketed to polish and fill scratches:

- Johnson Paste Wax
- Novus Plastic Polish #1 & #2 (Novus, Inc., Minneapolis, MN)
- Mirror Glaze Plastic Polish (M.G. M10) (Mirror Bright Polish Co., Pasadena, CA)

## **GRAFFITI & PAINT REMOVAL**

The following products can be used for removing graffiti or paint from the LEXAN™ panel:

- Butyl cellosolve
- Masking tape, adhesive tape or lint removal tools work well for lifting off old weathered paints

## **IMPORTANT CLEANING "DON'TS"**

- DO NOT use abrasive or highly alkaline cleaners.
- Never scrape LEXAN™ with squeegees, razor blades or other sharp instruments.
- Benzene, gasoline acetone or carbon tetrachloride should never be used.
- DO NOT clean LEXAN™ in hot sun or at elevated temperatures.